



ECO-POWER POWER SUPPLY 1-PHASE,

IN: 90-264 VAC OUT: 24V/1,3ADC

INPUT: 90...264 V AC
OUTPUT: 24 V DC $\pm 1\%$
Current: 1.3 A

[Link to Product](#)

Illustration



Product may differ from Image



Input	
Input voltage	100...240 V AC
Primary fusing external	max. 16 A
Input current	0.7 A (115 V AC); 0.4 A (230 V AC)
Inrush current after 1 ms	max. 20 A
Frequency	50...60 Hz
Output	

Output voltage	24 V DC $\pm 1\%$
LED display	LED (green) for output voltage
Output current	1.3 A (+40 °C); 1.04 A (+50 °C)
Mains failure bridging time	min. 10 ms (115 V AC); min. 90 ms (230 V AC)
Ripple	max. 20 mV eff/rms
Spikes	max. 100 mV ss/pp
Unit protection	short-circuit and overload protected
Parallel usage/serial usage	no/yes (max. 2 units)

General data

Standards	IEC 61010-2-201, EN 61204-3, EN 55011 B
Mounting method	screw fixing, M3
Temperature range	0...+40 °C, ...+50 °C derating (storage temperature -20...+85 °C)
Relative humidity	20...90%, no condensation
Efficiency	85% (115 V AC); 85% (230 V AC)
Dimensions H×W×D	36×77×105 mm