

# FL SWITCH 1001T-4POE - Industrial Ethernet Switch



2891064

<https://www.phoenixcontact.com/pc/products/2891064>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



PoE+ Ethernet switch conforms to IEEE 802.3at. Includes four PoE+ ports and one standard RJ45 port, all with 10/100 Mbps speeds.

## Your advantages

- Wide-range power supply of 18 ... 57 V DC
- Autocrossing
- Wide -40° ... +75°C temperature range
- Redundant power supply
- POE status LED per port
- Auto negotiation
- Automatic detection of IEEE 802.3at or 802.3af powered devices

## Commercial Data

Item number	2891064
Packing unit	1 pc
Minimum order quantity	1 pc
Product Key	DNN115
Catalog Page	Page 302 (C-6-2019)
GTIN	4046356764322
Weight per Piece (including packing)	753.5 g
Weight per Piece (excluding packing)	685 g
Customs tariff number	85176200
Country of origin	TW

# FL SWITCH 1001T-4POE - Industrial Ethernet Switch



2891064

<https://www.phoenixcontact.com/pc/products/2891064>

## Technical Data

### Dimensions

Width	55 mm
Height	117 mm
Depth	78 mm

### Notes

General	Mode B PoE
Utilization restriction	
EMC note	EMC: class A product, see manufacturer's declaration in the download area

### Material specifications

Housing material	Aluminum
------------------	----------

### Mounting

Mounting type	DIN rail mounting
---------------	-------------------

### Interfaces

#### Ethernet

Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100 Mbps
Transmission physics	Ethernet RJ45
Transmission length	100 m (Between transmitter / receiver)
Signal LEDs	LNK/ACT, 100, POE
No. of channels	1 (RJ45 port)

#### Ethernet (PoE)

Connection method	RJ45
Transmission speed	10/100 Mbps
Transmission physics	Ethernet RJ45
Transmission length	100 m (Between transmitter / receiver)
Signal LEDs	LNK/ACT, 100, POE
No. of channels	4 (RJ45 ports)

### Product properties

Type	Stand-Alone
Product type	Switch
Product family	Unmanaged PoE Switches 1000
MTTF	68 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)

# FL SWITCH 1001T-4POE - Industrial Ethernet Switch



2891064

<https://www.phoenixcontact.com/pc/products/2891064>

## Switch functions

Basic functions	PSE, complies with IEEE 802.3at
Signal contact control voltage	24 V DC
Signal contact control current	100 mA
Status and diagnostic indicators	LEDs: U <sub>S1</sub> , U <sub>S2</sub> (redundant voltage supply), Alarm (alarm contact), Link/Activity and PoE per Ethernet port
Additional functions	Autonegotiation

## Security functions

Basic functions	PSE, complies with IEEE 802.3at
-----------------	---------------------------------

## Electrical properties

Power consumption	129 W
Local diagnostics	US1, US2 Supply voltage Green LED
	PoE PoE detection Yellow LED
	LNK/ACT Link status/data transmission Green LED
	Alarm Power failure at US1 or US2/Link failure
Maximum power dissipation for nominal condition	129.6 W
Test section	Supply voltage/functional ground 500 V AC 1 min.
Transmission medium	Copper

## Supply

Supply voltage (DC)	24 V DC
Supply voltage range	18 V DC ... 57 V DC
Power supply connection	Via COMBICON, max. conductor cross section 2.5 mm <sup>2</sup>
Inrush current	18 A (57 V DC for 100 µs)
	10 A (24 V DC for 100 µs)
Residual ripple	3.6 V <sub>PP</sub> (within the permitted voltage range)
Max. current consumption	6.2 A (Maximum, nominal load)
Typical current consumption	148 mA (at U <sub>S</sub> = 24 V DC)

## Function

Signal contact control voltage	24 V DC
Signal contact control current	100 mA

## Connection data

### Connection technology

Connection name	Power supply
pluggable	yes

### Power supply

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

# FL SWITCH 1001T-4POE - Industrial Ethernet Switch



2891064

<https://www.phoenixcontact.com/pc/products/2891064>

Stripping length	7 mm
------------------	------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)

## EMC data

Conformance with EMC directives	IEC 61000-6-2 IEC 61000-4-2 (ESD) Criterion B
	IEC 61000-4-3 (immunity to radiated interference) Criterion A
	IEC 61000-4-4 (burst) Criterion B
	IEC 61000-4-5 (surge) Criterion B
	IEC 61000-4-6 (immunity to conducted interference) Criterion A
	IEC 61000-4-8 (immunity to magnetic fields) Criterion A
Electromagnetic compatibility	EN 55022 (emitted interference) Criterion A
	Conformance with EMC Directive 2004/108/EC

## System properties

### Functionality

Basic functions	PSE, complies with IEEE 802.3at
-----------------	---------------------------------

## Signaling

Status display	LEDs: U <sub>S1</sub> , U <sub>S2</sub> (redundant voltage supply), Alarm (alarm contact), Link/Activity and PoE per Ethernet port
----------------	--

# FL SWITCH 1001T-4POE - Industrial Ethernet Switch



2891064

<https://www.phoenixcontact.com/pc/products/2891064>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2891064>



**EAC**

Approval ID: RU \*-DE.A\*08.B.00739



**UL Listed**

Approval ID: FILE E 140324



**cUL Listed**

Approval ID: FILE E 140324



**KC**

Approval ID: MSIP-REI-PCK-2891064

# FL SWITCH 1001T-4POE - Industrial Ethernet Switch



2891064

<https://www.phoenixcontact.com/pc/products/2891064>

## Classifications

### ECLASS

ECLASS-11.0	19170402
ECLASS-12.0	19170402
ECLASS-13.0	19170402

### ETIM

ETIM 8.0	EC000734
----------	----------

### UNSPSC

UNSPSC 21.0	43222600
-------------	----------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)